



**Putzmeister**

## Your benefits

- Maintenance and service-friendly: everything is protected below the canopy
- Operating panel ergonomical on one side
- Large hopper 280 l with rubber collar and protective grid
- Piston pump unit extremely robust
- Chassis for road use with automatic brake adjustment
- Supporting feet for secure stability
- Made in Germany

## P 715 – Reliable, powerful and mobile for a wide range of applications



Self levelling floor screed

- Calcium sulphate screed
- Cement floor screed



Shotcrete

- Shotcrete



Fine grained concrete

- Conveying fine grained concrete
- Grouting work



The P 715 can reliably convey up to 16 mm pumpable media over considerable distances. The powerful piston pump is ideal for shotcrete and liquid screed applications.

With a delivery pressure of up to 68 bar and an output of 18 m<sup>3</sup>/h, it is a real power pump, despite its small dimensions and low weight.

Your expert Putzmeister dealer will be happy to explain the additional advantages to you and answer all your questions with regard to your individual requirements.



Fine concrete pumps like the P 715 are among the most versatile systems. You can use them for shotcrete or for pumping fine concrete of up to 16 mm.



Two drive versions: Reliable oil-cooled 3-cylinder Deutz diesel engine complies with exhaust emission regulation (Stage 3A) or low-noise, environmentally friendly electric motor (30 kW)



The easy to read, analog instruments and robust switches are protected by a sturdy flap against dirt and the risk of being damaged.

## Technical data

### P 715 TD / SD

### P 715 TE / SE

<b>Feed hopper</b>	250 l bzw. 280 l (with rubber attachment collar)	
<b>Theoretical delivery rate*</b>	4–17.4 m <sup>3</sup> /h	4–18.2 m <sup>3</sup> /h
<b>Delivery pressure</b>	68 bar	68 bar
<b>Delivery range**</b>	max. 300 m horizontal and 100 m vertical; with shotcrete/fine grained concrete, max. 100 m horizontal and 80 m vertical	
<b>Piston pump</b>	Hydraulic, 2-cylinder	
<b>Cylinder diameter</b>	150 mm	150 mm
<b>Drive</b>	3-cylinder Deutz diesel engine, D L03 2011, 34.5 kW	30 kW electric motor, 400 V, 50 Hz
<b>Drive cylinder diameter</b>	80/45 mm	80/45 mm
<b>Piston stroke</b>	700 mm	700 mm
<b>Min. strokes</b>	27	27
<b>Weight</b>	1850 kg (TD) / 1700 kg (SD)	1800 kg (TE) / 1650 kg (SE)
<b>Length x width x height</b>	4600 x 1520 x 1750 mm (TD) 2950 x 1400 x 1550 mm (SD)	4600 x 1520 x 1650 mm (TE) 2950 x 1400 x 1400 mm (SE)
<b>Filling height</b>	1180 mm (TD) / 973 mm (SD)	1180 mm (TE) / 973 mm (SE)
<b>Maximum particle size</b>	16 mm	16 mm
<b>Machine model</b>	Trailer pump (TD and TE), Stationary pump (SD and SE)	
<b>Chassis</b>	T chassis 1900 kg (TD and TE), runner (SD and SE)	

\* The delivery rate is theoretical and depends on the pump pressure.

\*\* The data is based on experience and is dependent on the materials used.

## Equipment

Autom. brake adjustment	■
Car fuse	■
Clamp coupling with sealing 4,5"	■
Cleaning tool	■
Instruction manual and spare parts list	■
Protective grid	■
Protective helmet	■
Rubber collar	■
Tool box with tool	■
Vibrator	■
Additive metering	□
Air vessel (self levelling floor screed)	□
Cable remote control	□
Central lubrication system	□
Chassis 2,5 t	□
Customer labelling	□
Exhaust flap	□
Flushing water pump	□
High-pressure cleaner	□
Lifting eye	□
Light holder 24 V	□
Particle filter	□
Radio remote control	□
Special canopy paint in RAL colours	□
Stroke counter	□
Working light	□
Zero report for hopper	□

□ Option    ■ Standard

## Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany  
 P.O.Box 2152 · 72629 Aichtal / Germany  
 Tel. +49 7127 599-0 · Fax +49 7127 599-743  
 mm@pmw.de · www.pmmortar.de

